

Multisplit R32 Casetes 4Vias



Incluido

9 000 Btu/h
12 000 Btu/h
18 000 Btu/h
24 000 Btu/h

Unidad interior			HCCI-66CC09DC4	HCCI-66CC12DC4	HCCI-66CC18DC4	HCCI-66CC24DC4
Capacidad	Nominal - Refrigeración	kW	2.6	3.5	5.0	7.1
	Nominal - Calefacción	kW	3.2	4	5.5	8
Parámetros Eléctricos	Alimentación eléctrica	Ph/V/Hz	1/220 ~ 240/50/60	1/220 ~ 240/50/60	1/220 ~ 240/50/60	1/220 ~ 240/50/60
Prestaciones	Flujo de aire	m³/h	510/450/390	620/520/420	700/600/500	1260/1070/820
	N. de potencia del sonido	dB(A)	50	52	57	55
	N. de presión del sonido	dB(A)	31/28/25	35/32/30	42/37/35	36/33/29
Instalación	Dimensiones (L/P/A)	mm	570/570/260	570/570/260	570/570/260	840/840/204
	Dimensiones embalaje (L/P/A)	mm	718/680/380	718/680/380	718/680/380	990/990/310
	Peso neto/ total	kg	17/20	18.5/22	18.5/22	27/31
	Diámetro tubería - líquido	mm (pol)	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")	9.52 (3/8")
	Diámetro tubería - gas	mm (pol)	9.52 (3/8")	9.52 (3/8")	12.7 (1/2")	15.88 (1/2")
Panel	Dimensiones (L/P/A)	mm	700/700/60	700/700/60	700/700/60	950/950/50
	Dimensiones embalaje (L/P/A)	mm	740/750/115	740/750/115	740/750/115	1000/1000/110
	Peso neto/ total	kg	2.8/4.8	2.8/4.8	2.8/4.8	6.5/9